

LeaderTHERM NXT 1010

LeaderTHERM NXT

DESCRIPTION

LeaderTHERM NXT 1010 consists of specially treated phlogopite mica structured layer material in combination with a grooved LeaderKAM Kammprofile carrier ring. The gasket can be supplied with or without outer ring. To suit specific applications it is possible to select special materials.

APPLICATION

High temperature ; Exhaust manifolds and systems, gas

turbines, gas and oil burners, heat exchangers,

CHEMICAL COMPATIBILITY

Broad chemical resistance.

DELIVERY OPTIONS

In all Kamprofile configurations KV, KV9 and KV9L

TEMPERATURE

APPROVALS & CERTIFICATES

- BAM

TECHNICAL DATA

max Temperature [°C]	1000
min Temperature [°C]	N/A
max Pressure [bar]	300
density [g/cm ³]	1.2
Minimum initial stress [DIN E 2505 part 2] [N/mm ²]	25
Maximum initial stress [DIN E 2505 part 2] [N/mm ²]	500
M-Value	3.5
Y- Value [psi]	3000
Gasket required flange roughness [Ra micron]	3,2-6,3
Gasket required flange roughness [RMS]	125-250
max Seating stress [Q _{max} bei RT EN13555] [n/mm ²]	500

LOCATIONS

850 Sense Road LA PORTE, TX 77571, USA GLOBAL HEADQUARTERS

8622 South Choctaw Drive BATON ROUGE, LA, USA 70815

Pšurnovická cesta 1026, 01401 BYTCA, Republic of Slovakia EUROPE HEADQUARTERS

PHONE

+1 281 542 0600

+1 225 275 8000

+421 41 553 2686

FAX

+1 281 542 5552

+1 225 273 9073

+421 41 553 2895